



Figure similar

Data sheet for Active Interface Modules Booksize

Article No. : 6SL3100-0BE28-0AB0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Electrical data

|                  |               |
|------------------|---------------|
| Number of phases | 3 AC          |
| Line voltage     | 380 ... 480 V |

Connections

Line side

|                         |                                     |
|-------------------------|-------------------------------------|
| Design                  | M8 bolt                             |
| Conductor cross-section | 2.5 ... 120 mm² (AWG 14 ... AWG -3) |
| PE conductor            | M8 Screw                            |

Mechanical data

|                      |                     |
|----------------------|---------------------|
| Degree of protection | IP20 / UL open type |
| Type of construction | Booksize            |
| Net weight           | 31.9 kg (70.33 lb)  |

Dimensions

|        |                   |
|--------|-------------------|
| Width  | 300 mm (11.81 in) |
| Height | 380 mm (14.96 in) |
| Depth  | 270 mm (10.63 in) |

Standards

|                           |       |
|---------------------------|-------|
| Compliance with standards | cURus |
|---------------------------|-------|

Rated data

|   |        |
|---|--------|
| Input current                           | 128 A  |
| Current requirement at 24 V DC, maximum | 1.20 A |

General technical specifications

|                      |          |
|----------------------|----------|
| Sound pressure level | 68 dB    |
| Losses               | 0.490 kW |

Ambient conditions

|                        |                          |
|------------------------|--------------------------|
| Cooling air throughput | 0.167 m³/s (5.900 ft³/s) |
| Type of cooling        | Internal air cooling     |